

ECORocks[®]



ECORocks, spa/exercise area, Radisson Hotel Fargo, ND
Architect: Adams Development

Classic rock n' rubber.

Create designs that rock with Ecorocks, the floor that looks like polished terrazzo but without all the hassles. Ten rock-on colors include naturally-inspired shades and new neutrals that get it on perfectly with today's global design materials including exotic hardwoods. Resilient Ecorocks is comfortable underfoot and acoustical for environmentally sound interiors.

Various Dimensions


- | | |
|-------|---|
| Rolls | 48" x 5/32" (4 mm standard) |
| | 48" x 1/4" (6 mm special- 5,000 sq. ft. min.) |
| | Standard 50' rolls |
| Tiles | 36" x 36" |
| | 18" x 18" |
| | Available in 4 mm standard; 6 mm special |



ECOrocks Color Line




#902
Pebble Beach



#903
Big Boulder




#905
Granite Run



#906
Lava Rock




#907
Horseshoe Bay




#908
North Shore




#909
All Shook Up



#910
Jail House Rock



#911
Zuma



#912
Rocqua

Colors may vary. Please specify from actual samples obtained from your local sales representative or Gerbert, Ltd.

Physical Data

Test	ASTM	Result
Tensile Strength	D412	200 lb/in ² min*
Flexibility	F137	Pass 1/4 inch mandrel
Coefficient of Friction	D2047	>0.9
Thermal Conductivity	C518	0.445 Btu-in/hr-ft ² -°F
Static Load Limit	F970, 400 lbs	<0.005 in
Chemical Resistance	F925	slight change
Impact Insulation Class	E492	48
Sound Transmission Coefficient	E413	51
Noise Reduction Coefficient	C423	0.05 sabine/ft ²
Sustainability	E2129-01	data collected
CHPS Section 01350	D5116	pass

*150 lb/in² min for ECOrocks

Brief Architectural Specifications

ECOsurfaces Commercial Recycled Rubber Flooring:

The single-ply, rubber surface furnished under this specification shall be ECORE's _____ (specify one of the ECOsurfaces products listed below).

ECOrocks is a non-laminated, single-ply surface made from medium and jumbo sized reprocessed EPDM rubber to create a terrazzo look. The color shall be (specify: color number and name).

ECOsurfaces rolled products shall be 4' wide. The rolled rubber surface will have an overall thickness of _____ (specify: 5/32" [4 mm] standard, 1/4" [6 mm] special order - 5000 sq. ft. min.).

ECOsurfaces tile products shall be _____ (specify: 18" x 18" or 36" x 36" and thickness of 5/32" [4 mm] or 1/4" [6 mm]).

ECOsurfaces shall meet standards specified under the LEED® (Leadership in Energy and Environmental Design) criteria developed by the U.S. Green Building Council (USGBC).

For the ECORE International™ warranty to apply, only use recommended adhesive and follow all ECORE approved installation and maintenance procedures. The rubber flooring shall comply with the Americans with Disabilities Act (ADA) regulations.

Technical Data: For complete guide specifications, log on to www.ecosurfaces.com or call 1-877-326-7873.

Installation

Basic installation procedures and tools are the same as other standard commercial resilient flooring. ECOsurfaces should be installed by experienced floor covering mechanics. Instructions in the ECOsurfaces installation manual should be followed and are available at www.ecosurfaces.com or through your ECOsurfaces representative.

Cleaning and Maintenance

All ECOsurfaces flooring systems must be maintained as recommended. The type and frequency of maintenance will vary according to maintenance equipment and desired appearance of product. Detailed maintenance instructions are available at www.ecosurfaces.com or through your ECOsurfaces representative.

Warranty

ECOsurfaces is guaranteed by ECORE to be free of manufacturing defects in both material and workmanship. If such a defect is discovered, the customer must notify ECORE directly or through the contracting installer or distributor. If found to be defective within five years, the sole remedy against the seller will be either the replacement or repair of the defective goods, or at the seller's option, credit may be issued not exceeding the selling price of the defective goods.

The ECOsurfaces warranty shall not cover dissatisfaction due to improper maintenance or installation, damage from improper maintenance or usage or general misuse, including, without limitation, burns, cuts, tears, scratches, scuffs, indentation damage from high heels, rolling loads, damage or discoloration from floor care products not recommended by either Gerbert Ltd. or ECORE, extended exposure to direct sunlight or differences in color between samples or photographs and actual flooring.

Manufactured by ECORE International • Distributed by Gerbert Ltd.